



Custom Track Service Percent Worn

HOLT TEXAS LTD.

HOWARDMCANEAR EQUIPMENT
(0585540)

Prepared By: Christopher Thornton

Model	D6TLGP	Job Site	Howard McAnear Longview Yard	Inspection Date	21-Aug-2020
Manufacturer	Caterpillar			Next Inspection Date	--
Serial Number	HTZ00373		<u>Left</u> <u>Right</u>	Next Inspection Hours	--
Reference Number	Htz373	Track Sag (1.8 in - 2.6 in)	-- --	Underfoot Conditions	
Hour Meter Reading	2,610.3	Frame Ext (max 5.6 in)	3.6 in 3.8 in	Impact	Moderate
Hours Per Week	14.75	Dry Joints	-- --	Abrasion	Moderate
Total Odometer Reading	--	Internal Wear	0% 0%	Moisture	Moderate
Forward Odometer	--		32 in 32 in	Packing	Moderate
Reverse Odometer	--			Bushing Allowable Wear	Greater
				Link Allowable Wear	Greater

Position	Part Number		Status		Date Installed		SMU Installed		Hours on Wear Surface		Measurement (inches)		Percent Worn		
	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	
Track Link															
Left Link Assembly:4240847				Right Link Assembly:4240847											
	3788241	3788241	Original	Original	26Apr20	26Apr20	--	--	--	--	1.41 (U)	1.44 (U)	56%	50%	
Track Bushing															
	8E7222	8E7222	Original	Original	26Apr20	26Apr20	--	--	--	--	0.51 (U)	0.49 (U)	8%	16%	
Track Shoe															
Left Width:36in						Right Width:36in									
	1967839	1967839	Original	Original	26Apr20	26Apr20	--	--	--	--	2.44 (U)	2.4 (U)	44%	46%	
Idlers															
Front	2024296	2024296	Original	Original	26Apr20	26Apr20	--	--	--	--	1.2 (D)	1.19 (D)	50%	49%	
Rear	2024296	2024296	Original	Original	26Apr20	26Apr20	--	--	--	--	1.16 (D)	1.16 (D)	44%	44%	
Carrier Roller															
Front	2355974	2355974	Original	Original	26Apr20	26Apr20	--	--	--	--	7.7 (C)	7.66 (C)	14%	18%	
Track Roller															
Front	S	2880934	2880934	Original	Original	26Apr20	26Apr20	--	--	--	--	1.53 (U)	1.53 (U)	52%	52%
2	D	2880935	2880935	Original	Original	26Apr20	26Apr20	--	--	--	--	1.63 (U)	1.64 (U)	38%	36%
3	S	2880934	2880934	Original	Original	26Apr20	26Apr20	--	--	--	--	1.6 (U)	1.61 (U)	42%	40%
4	D	2880935	2880935	Original	Original	26Apr20	26Apr20	--	--	--	--	--	--	--	--
CONDITION: Guarded							CONDITION: Guarded								
5	D	2880935	2880935	Original	Original	26Apr20	26Apr20	--	--	--	--	1.62 (U)	1.6 (U)	39%	42%
6	S	2880934	2880934	Original	Original	26Apr20	26Apr20	--	--	--	--	1.64 (U)	1.64 (U)	36%	36%

7	D	2880935	2880935	Original	Original	26Apr20	26Apr20	--	--	--	--	1.64 (U)	1.63 (U)	36%	38%
8	S	2880934	2880934	Original	Original	26Apr20	26Apr20	--	--	--	--	1.49 (U)	1.5 (U)	59%	57%
Sprocket															
		1730946	1730946	Original	Original	26Apr20	26Apr20	--	--	--	--	8.72 (T)	8.7 (T)	18%	21%

(U) Ultrasonic I (C) Caliper I (D) Depth Gauge I (T) Tape

General Recommendations

--