



## Custom Track Service Percent Worn

**HOLT TEXAS LTD.**

HOWARDMCANEAR EQUIPMENT  
(0585540)

Prepared By: Matthew Davis

<b>Model</b>	D6NXL	<b>Job Site</b>	HM YARD		<b>Inspection Date</b>	05-Jan-2021
<b>Manufacturer</b>	Caterpillar		<u>Left</u>	<u>Right</u>	<b>Next Inspection Date</b>	--
<b>Serial Number</b>	PER00975	<b>Track Sag (46 mm - 66 mm)</b>	--	--	<b>Next Inspection Hours</b>	--
<b>Reference Number</b>	975	<b>Frame Ext (max 102 mm)</b>	55 mm	58 mm	<b><u>Underfoot Conditions</u></b>	
<b>Hour Meter Reading</b>	3,747	<b>Dry Joints</b>	--	--	<b>Impact</b>	Moderate
<b>Hours Per Week</b>	--	<b>Internal Wear</b>	--	--	<b>Abrasion</b>	Moderate
<b><u>Total Odometer Reading</u></b>	--		--	--	<b>Moisture</b>	Moderate
<b>Forward Odometer</b>	--				<b>Packing</b>	Moderate
<b>Reverse Odometer</b>	--				<b>Bushing Allowable Wear</b>	Greater
					<b>Link Allowable Wear</b>	Greater

Position	Part Number		Status		Date Installed		SMU Installed		Hours on Wear Surface		Measurement (mm)		Percent Worn		
	Component	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right
<b>Track Link</b>		<b>Left Link Assembly:1102976</b>						<b>Right Link Assembly:1102976</b>							
	1061625	1061625	Original	Original	--	--	--	--	--	--	35.2 (U)	35.6 (U)	35%	33%	
<b>Track Bushing</b>															
	1061618	1061618	Original	Original	--	--	--	--	--	--	9.4 (U)	9.8 (U)	52%	48%	
<b>Track Shoe</b>		<b>Left Width:560mm</b>						<b>Right Width:560mm</b>							
	1070713	1070713	Original	Original	--	--	--	--	--	--	69.6 (U)	69.8 (U)	25%	24%	
<b>Idlers</b>															
<b>Front</b>	1901546	1901546	Original	Original	--	--	--	--	--	--	26 (D)	26 (D)	16%	16%	
<b>Rear</b>	1901546	1901546	Original	Original	--	--	--	--	--	--	26 (D)	26 (D)	16%	16%	
<b>Carrier Roller</b>															
<b>Front</b>	2295446	2295446	Original	Original	--	--	--	--	--	--	175 (C)	176 (C)	18%	15%	
<b>Track Roller</b>															
<b>Front</b>	S	3104912	3104912	Original	Original	--	--	--	--	--	38.7 (U)	38.7 (U)	40%	40%	
<b>2</b>	D	3104915	3104915	Original	Original	--	--	--	--	--	38.5 (U)	38.2 (U)	40%	43%	
<b>3</b>	S	3104912	3104912	Original	Original	--	--	--	--	--	38.5 (U)	38.1 (U)	40%	43%	
<b>5</b>	S	3104912	3104912	Original	Original	--	--	--	--	--	37.9 (U)	38.6 (U)	44%	40%	
<b>6</b>	D	3104915	3104915	Original	Original	--	--	--	--	--	38.6 (U)	38.7 (U)	40%	40%	
<b>7</b>	S	3104912	3104912	Original	Original	--	--	--	--	--	37.9 (U)	38.5 (U)	44%	40%	
<b>Sprocket</b>															
	2520546	2520546	Original	Original	--	--	--	--	--	--	206 (T)	207 (T)	39%	35%	

(U) Ultrasonic | (C) Caliper | (D) Depth Gauge | (T) Tape

### General Recommendations

