



Custom Track Service Percent Worn

HOLT TEXAS LTD.

HOWARDMCANEAR EQUIPMENT
(0585540)

Prepared By: Christopher Thornton

Model	D6NLGP	Job Site	HM Yard Temple	Inspection Date	10-Nov-2020
Manufacturer	Caterpillar		Left Right	Next Inspection Date	--
Serial Number	PBA02913	Track Sag	-- --	Next Inspection Hours	--
Reference Number	PBA2913	(1.8 in - 2.6 in)		Underfoot Conditions	
Hour Meter Reading	4,261.3	Frame Ext (max 4.3 in)	1.9 in 2.2 in	Impact	Moderate
Hours Per Week	--	Dry Joints	-- --	Abrasion	Moderate
Total Odometer Reading	--	Internal Wear	0% 0%	Moisture	Moderate
Forward Odometer	--		29.95 in 29.95 in	Packing	Moderate
Reverse Odometer	--			Bushing Allowable Wear	Greater
				Link Allowable Wear	Greater

Position	Part Number		Status		Date Installed		SMU Installed		Hours on Wear Surface		Measurement (inches)		Percent Worn		
	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	
Track Link		Left Link Assembly:1061634				Right Link Assembly:1061634									
	1061625	1061625	Original	Original	09Nov20	09Nov20	--	--	--	--	1.44 (U)	1.44 (U)	23%	23%	
Track Bushing															
	1061618	1061618	Original	Original	09Nov20	09Nov20	--	--	--	--	0.46 (U)	0.46 (U)	20%	20%	
Track Shoe		Left Width:33.1in				Right Width:33.1in									
	3563429	3563429	Original	Original	09Nov20	09Nov20	--	--	--	--	2.77 (U)	2.73 (U)	23%	25%	
Idlers															
Front	1901546	1901546	Original	Original	09Nov20	09Nov20	--	--	--	--	1.03 (D)	1.04 (D)	18%	20%	
Rear	1901546	1901546	Original	Original	09Nov20	09Nov20	--	--	--	--	1.04 (D)	1.04 (D)	20%	20%	
Carrier Roller															
Front	2295446	2295446	Original	Original	09Nov20	09Nov20	--	--	--	--	6.88 (C)	6.88 (C)	19%	19%	
Track Roller															
Front	S	3104912	3104912	Original	Original	09Nov20	09Nov20	--	--	--	--	1.59 (U)	1.6 (U)	28%	27%
2	D	3104915	3104915	Original	Original	09Nov20	09Nov20	--	--	--	--	1.67 (U)	1.66 (U)	15%	17%
3	S	3104912	3104912	Original	Original	09Nov20	09Nov20	--	--	--	--	1.69 (U)	1.69 (U)	12%	12%
4	D	3104915	3104915	Original	Original	09Nov20	09Nov20	--	--	--	--	--	--	--	--
CONDITION: Guarded								CONDITION: Guarded							
5	D	3104915	3104915	Original	Original	09Nov20	09Nov20	--	--	--	--	--	--	--	--
CONDITION: Guarded								CONDITION: Guarded							
6	S	3104912	3104912	Original	Original	09Nov20	09Nov20	--	--	--	--	1.67 (U)	1.68 (U)	15%	13%
												1.65	1.66		

7	D	3104915	3104915	Original	Original	09Nov20	09Nov20	--	--	--	--	(U)	(U)	18%	17%
8	S	3104912	3104912	Original	Original	09Nov20	09Nov20	--	--	--	--	1.59 (U)	1.6 (U)	28%	27%
Sprocket															
		618077	618077	Original	Original	09Nov20	09Nov20	--	--	--	--	8.12 (T)	8.14 (T)	38%	36%

(U) Ultrasonic I (C) Caliper I (D) Depth Gauge I (T) Tape

General Recommendations

--